

Technical Specifications

WaterWorld 12-1700

Specifications of the WaterWorld 12-1700 lithium battery are listed below.
For more information please visit:
www.waterworldelectronics.com



General Features	
Article Number	WW-81012017
Nominal energy capacity	1700 Wh
Nominal capacity	133 Ah
Useable capacity	129 Ah
Capacity @25A	310 min
Nominal voltage	12,8 V
Charging voltage	14,2 V
Discharging voltage	10,8 V
Continuous discharge rate	150 A
Max quick charge	80 A
Max peak discharge rate (2s)	300 A
Max peak discharge rate (10s)	200 A
Weight	19 kg
Size (LxBxH)	242 x 253 x 223 mm
Size (excluding feet)	242 x 253 x 212 mm
Square shape volume	13 L
Bluetooth	Yes, iOS / Android
Case material	3.5 mm Aluminium

User Information	
Ambient temperature discharging	-18°C to 55°C
Ambient temperature charging	2°C to 45°C
Ambient temperature storage	-25°C to 55°C
Typical storage time at 50% SoC	40 weeks
Max connections	Up to 1 Series 8 Parallel
Protection class (excluding salt water)	IP67

Lifetime Data	
Cycle lifetime	>4000 cycles with 80% discharge depth at 25 °C to capacity loss of 20% at 0.5C
Average annual capacity loss	Approximately 2% at 25°C ambient temperature
Ideal storage temperature	10°C up to 30°C

Battery Composition	
Cell type	Cylindrical
Chemistry	LiFePo4
Capacity per cell	6,05 Ah
Nominal voltage per cell	3,2 V
Cell configuration	4s22p

Battery Management and Safety	
On-off switch	Yes
Terminals	M8 screw F
Cell balancing, passive	Yes
High current and short circuit protection	Yes, up to 1500 A
Deep discharge protection	Yes
Protection against polarity reversal	Yes
Individual cell string voltage monitoring	Yes
Safety vent for each cell	Yes
Cell temperature monitoring	Yes
Temperature monitoring battery electronics	Yes
Shipping classification	UN3480 CLASS 9
Certifications/ compliance battery	CE UN38.3 RoHS
Certifications/ compliance battery cells	UL CE IEC62133 IEC62619 EC61960 BIS PSE RoHS UN38.3