

Features

- Standard throttle and colour display included
- Extremely quiet operation
- Low maintenance
- Air-cooled system
- Standard warranty 2 years*


* 3-year warranty when combining the WaterWorld electric inboard system with WaterWorld lithium batteries.



Standard throttle



Display



Relay
(only for 10.0i and 20.0i)



4.0i

Length	525 mm
Width	240 mm
Height	229 mm
Weight	34 kg
Nominal speed	1500 rpm
Maximum power	4.4 kW
Nominal voltage	48 Volt
Maximum current	85 Ampère
Max. temperature motor	140 °C
Max. temperature controller	88 °C
Type	Asynchronous
Control mode	Sensorless
IP rating motor	IP 65
IP rating controller	IP 65
Communication	CANopen
Hybrid possible	Yes
Regeneration possible	Yes



10.0i

Length	719 mm
Width	290 mm
Height	296 mm
Weight	76 kg
Nominal speed	1500 rpm
Maximum power	11 kW
Nominal voltage	48 Volt
Maximum current	200 Ampère
Max. temperature motor	140 °C
Max. temperature controller	88 °C
Type	Asynchronous
Control mode	Sensorless
IP rating motor	IP 65
IP rating controller	IP 65
Communication	CANopen
Hybrid possible	Yes
Regeneration possible	Yes



20.0i

Length	769 mm
Width	290 mm
Height	301 mm
Weight	100 kg
Nominal speed	1600 rpm
Maximum power	20 kW
Nominal voltage	48 Volt
Maximum current	400 Ampère
Max. temperature motor	140 °C
Max. temperature controller	88 °C
Type	Asynchronous
Control mode	Sensorless
IP rating motor	IP 65
IP rating controller	IP 65
Communication	CANopen
Hybrid possible	Yes
Regeneration possible	Yes