

Features

- Standard throttle and colour display included
- Unmatched maneuverability
- Low maintenance
- Quiet operation
- Ultimate flexibility
- Standard warranty 2 years*


* 3-year warranty when combining the WaterWorld electric inboard system with WaterWorld lithium batteries.



Standard throttle



Display



Relay
(only for 8.0p and 18.0p)



2.0p

Length 496 mm
Width 108 mm
Height 255 mm
Weight 16 kg

Nominal speed 1500 rpm
Maximum power 2.2 kW
Nominal voltage 48 Volt
Maximum current 45 Ampère
Max. °C motor 120 °C
Max. °C controller 88 °C
Cooling motor Water-cooled
Cooling controller Air-cooled

Type Permanent magnet

Control mode Sensor

IP rating POD underwater IP 9X**

IP rating controller IP 65

Communication CANopen

Regeneration possible Yes

Mounting Fixed and steerable



3.5p

Length 525 mm
Width 108 mm
Height 255 mm
Weight 16 kg

Nominal speed 1500 rpm
Maximum power 3.8 kW
Nominal voltage 48 Volt
Maximum current 80 Ampère
Max. °C motor 120 °C
Max. °C controller 88 °C
Cooling motor Water-cooled
Cooling controller Air-cooled

Type Permanent magnet

Control mode Sensor

IP rating POD underwater IP 9X**

IP rating controller IP 65

Communication CANopen

Regeneration possible Yes

Mounting Fixed and steerable



8.0p

Length 652 mm
Width 150 mm
Height 288 mm
Weight 35 kg

Nominal speed 1500 rpm
Maximum power 8.8 kW
Nominal voltage 48 Volt
Maximum current 180 Ampère
Max. °C motor 120 °C
Max. °C controller 88 °C
Cooling motor Water-cooled
Cooling controller Air-cooled

Type Permanent magnet

Control mode Sensor

IP rating POD underwater IP 9X**

IP rating controller IP 65

Communication CANopen

Regeneration possible Yes

Mounting Fixed and steerable



18.0p

Length 726 mm
Width 206 mm
Height 370 mm
Weight 71 kg

Nominal speed 1500 rpm
Maximum power 19.8 kW
Nominal voltage 48 Volt
Maximum current 400 Ampère
Max. °C motor 120 °C
Max. °C controller 88 °C
Cooling motor Water-cooled
Cooling controller Air-cooled

Type Permanent magnet

Control mode Sensor

IP rating POD underwater IP 9X**

IP rating controller IP 65

Communication CANopen

Regeneration possible Yes

Mounting Fixed and steerable