Technical Specifications

WaterWorld 24-6800

Specifications of the WaterWorld 24-6800 lithium battery are listed below. For more information please visit:

www.waterworldelectronics.com









General Features	
Capacity	6800 Wh
Nominal voltage	25.6 V
Final charging voltage	28.4 V
Final discharging voltage	21.6 V
Continuous discharge rate	150 A
Max peak discharge rate (10s)	200 A
Weight	61 kg
Dimensions incl sockets (LxBxH)	683 mm x 253 mm x 213 mm
Volume	63.8 L
Battery chemistry	Lithium iron phosphate (LFP) LiFePO4

Use Information		
Ambient temperature, discharging	-15°C up to +45°C	
Ambient temperature, charging	+2°C up to +45°C	
Ambient temperature, storage	-25°C up to +55°C	
Typical storage time at 50% SOC	40 weeks without any load (battery turned off)	
Max connections	Up to 1 Series 8 Parallel	
Max quick charge	130 A	
Protection class	IP67	

Battery Composition		
Cell type	Cylindrical	
Capacity per cell	6.05 Ah	
Nominal voltage per cell	3.2 V	
Cell connection	8S 44P	

Battery Management and Safety		
On-off switch	Yes	
Cell balancing	Yes	
High current and short-circuit protection	Yes, up to 1500A	
Deep discharge protection	Yes, cut off at 21.6 V	
Protection against polarity reversal	Yes	
Individual cell string voltage monitoring	Yes	
Safety vent for each cell	Yes	
Cell temperature monitoring	Yes	
Temperature monitoring of battery electronics	Yes	
Low temperature shut off	Yes	
High temperature shut off	Yes	

Lifetime Data		
Cycle lifetime	>4000 cycles with 80% discharge depth at 25 °C to capacity loss of 20% at 0.5C	
Average annual capacity loss	Approximately 2% at 25°C ambient temperature	
Ideal storage temperature	10°C - 30°C	