Technical Specifications WaterWorld 24-3400

Specifications of the WaterWorld 24-3400 lithium battery are listed below. For more information please visit: www.waterworldelectronics.com

General Features		
Article Number	WW-81024034	
Nominal energy capacity	3400 Wh	
Nominal capacity	133 Ah	
Useable capacity	129 Ah	
Capacity @25A	310 min	
Nominal voltage	25,6 V	
Charging voltage	28,4 V	
Discharging voltage	21,6 V	
Continuous discharge rate	150 A	
Max quick charge	80 A	
Max peak discharge rate (2s)	300 A	
Max peak discharge rate (10s)	200 A	
Weight	34 kg	
Size (LxBxH)	392 x 253 x 223 mm	
Size (LxBxH, excluding feet)	392 x 253 x 212 mm	
Square shape Volume	21 L	
Bluetooth	Yes, iOS / Android	
Case material	3,5 mm Aluminium	

User Information		
Ambient temperature discharging	-18°C to 55°C	
Ambient temperature charging	2°C to 45°C	
Ambient temperature storage	-25°C to 55°C	
Typical storage time at 50% SoC	40 weeks	
Max connections	Up to 2 Series 8 Parallel	
Protection class (excluding salt water)	IP67	

Lifetime Data		
Cycle lifetime	>4000 cycles with 80% discharge depth at 25 °C to capacity loss of 20% at 0,5C	
Average annual capacity loss	Approximately 2% at 25°C ambient temperature	
Ideal storage temperature	10°C up to 30°C	





Battery Composition		
Cell type	Cylindrical	
Chemistry	LiFePo4	
Capacity per cell	6,05 Ah	
Nominal voltage per cell	3,2 V	
Cell configuration	8s 22p	

Battery Management and Safety		
On-off switch	Yes	
Terminals	M8 Screw F	
Cell balancing, passive	Yes	
High current and short-circuit protection	Yes, up to 1500 A	
Deep discharge protection	Yes	
Protection against polarity reversal	Yes	
Individual cell string voltage monitoring	Yes	
Safety vent for each cell	Yes	
Cell temperature monitoring	Yes	
Temperature monitoring battery electronics	Yes	
Shipping classification	UN3480 CLASS 9	
Certifications/ compliance battery	CE UN38.3 RoHS	
Certifications/ compliance battery cells	UL CE IEC62133 IEC62619 EC61960 BIS PSE RoHS UN38.3	

*Visit www.waterworldelectronics.com for the latest version of this document as specification may change.